

2020 Popular Factory Direct Price 4/8/16CH 5M-N Standalone DVR CMS H.265 AHD DVR System



Model No.	WDM-DVR6504M-N	WDM-DVR6508M-N	WDM-DVR6516M-N
Specifications			
Processor	Hi3520DV400	Hi3520DV400	Hi3521D
Video compression	H.265		
Solution	4*5M-N@15fps(6 in 1); 4*4M-N@18fps (6 in 1); 4*1080P@18fps (6 in 1)	8*5M-N@15fps(6 in 1); 8*4M-N@18fps (6 in 1); 8*1080P@18fps (6 in 1)	16*5M-N@6fps(6 in 1); 16*4M-N@8fps (6 in 1); 16*1080N@25fps (6 in 1)
Analog video input	4PCS BNC Port(Level:1.0Vp-p, impedance:75Ω)	8PCS BNC Port(Level:1.0Vp-p, impedance:75Ω)	16PCS BNC Port(Level:1.0Vp-p, impedance: 75Ω)
Audio compression	ADPCM		
Audio input	1PCS RCA Port(Level: 2.0Vp-p,impedance: 1kΩ)	1PCS RCA Port(Level:2.0Vp-p, impedance:1kΩ)	1PCS RCA Port(Level: 2.0Vp-p, impedance: 1kΩ)
Video/Audio output			
Multi-mode switch	Analog: 4CH*5MP, 4CH*1080P @18fps	Analog: 8CH*5M-N; 8*1080P@18fps	Analog: 16*5M-N; 16*4MP; 8*1080N@18fps
	IP: 16*1080P; 4*5MP	IP: 8*1080P; 8*5MP	IP: 8*1080P; 4*5MP;4*3MP
	Blend: 2*1080P(Analog)+2*1080P(IP); 4*1080N+4*960P	Blend: 4*1080P(Analog)+4*1080P(IP)	Blend: 8*1080N(Analog)+8*960P
VGA output	Max 1080P		
HDMI output	Max 5MP		
CVBS output	NO		
Frame rate	NTSC:1~30FPS/S;PAL:1~25FPS/S		
Video bit rate	256kps/384Kbps/512Kbps/640kbps/768Kbps/1M/1.5M/2M/2.5M/3M/4M/5M/6M/8M		
Video output	1CH video out		
Audio output	1PCS RCA Port(line level , impedance : 1kΩ)		
Dual-stream	YES		
Stream type	combine streams/ video stream		
Playback Channel	4chs	4chs	16chs
Hard disk	1 SATA		
Capacity	each port support max 8TB HDD		
External interface			
Network interface	1PCS RJ45 10M / 100M/1000M adaptive Ethernet port		
Audio	4/1	4/1	2/1
Alarm	0/0	0/0	1/1
USB interface	2*USB2.0, USB mouse		
Remote control	NO		
General			
Mobile App	Xmeye		
Support	Support VGA,PTZ,HDMI		
Power supply	DC12V2A		
Working temperature	-10°C--+55°C		
Working humidity	10%--90%		
Chassis	1U	1U	1U
Dmensions(W×D×H)	35*27.5*7.5cm	35*27.5*7.5cm	44.5*30*9cm
Accessories			
Accessories	1pc power supply, 1pc CD, 1pc user manual, 4pcs screws		