



- * Support 4/8/16CH 5/8.0MP Encoding
- * Support XVI,AHD, TVI,CVI, CVBS, IP video input
- * Support VGA maximum 1080P output, HDMI up to 4K output
- * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- * Support the Onvif protocol
- * Support WEB, CMS, VMS, MYEYE Platform
- * Mobile phone remote monitoring (iOS, Android)
- * Cloud services, P2P, alarm information push to phone
- * Support for more than twenty languages

Specifications			
Product Name	4/8/16chs H.265+ 6 In 1 AHD TVI CVI CVBS 4K-N DVR Video Recorder Surveillance System		
Model No.	WDM-DVR6504K-N	WDM-DVR6508K-N	WDM-DVR6516K-N
System			
Processor	Hi3520DV400	Hi3521D	Hi3531D
Video			
Video compression	H.265+		
Encode	4*4K-N@15fps(6 in 1), 4*5M@12fps(6 in 1)	8*4K-N 15fps(6 in 1);8*5MP 12fps(6 in 1);	16*4K-N 15fps(6 in 1);16*5MP 12.5fps(6 in 1)
Decode	4*4K-N@15fps(6 in 1), 4*5M@12fps(6 in 1)	8*4K-N 15fps(6 in 1);8*5MP 12fps(6 in 1);	16*4K-N 15fps(6 in 1);16*5MP 12.5fps(6 in 1)
Multi-mode	Analog: 4*5MP/8MP(same channel, adaptive 8MP)	Analog: 8*5MP/8MP(same channel, adaptive 8MP)	Analog: 16*5MP/8MP(same channel, adaptive 8MP)
	Hybird: 2*4MP(analog)+2*4MP(IP)	Hybird: 4*AHD 4MP + 4*4MP(IP)	Hybird: 8*AHD 4MP + 8*4MP(IP)
	IP: 16*1080P; 16*960P; 4*5MP	IP: 8*1080P+8*960P; 4*5MP	IP: IP: 8*1080P+8*960P; 4*5MP
Playback	1*4K-N/1*5MP	2*4K-N/2*5MP	4*4K-N 4*5MP
Audio			
Audio compression	G.711A		
Management			
Record mode	Manual>Alarm>Motion detection>Timing		
Inquire mode	Inquire by Time/Calendar/Event/Channel		
Storage mode	HDD Storage, Network Storage		
Backup	Network, USB, SATA		
Interface			
Video Input	4*BNC (Support Coaxitron)	8*BNC (Support Coaxitron)	16*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:4K)		
VGA output	1*VGA (MAX:1080P)		
Audio In/Out	1/1	1/1	2/1
Alarm In/Out	0/0		
Ethernet	1*10/100Mbps Ethernet port, RJ45 port		
PTZ Control	1*RS485, Support for multiple PTZ protocol		
USB	2*USB2.0		
Remote Control	Optional		
HDD	1*SATA interface (Up to 8TB)		1*SATA interface For Standard (Up to 8TB) 2HDD also available
General			
Power supply	DC12V 2A		
Consumption	<15W(Without HDD)		
Working temperature	0°C--+55°C		
Working humidity	10%--90%		
Chassis	168mm*80mm		