



- * Support 32CH 4K-N/5MP unreal-time encoding
- * Support XVI,AHD, TVI,CVI, CVBS, IP video input
- * Support VGA maximum 1080P output, HDMI up to 4K output
- * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- * Support the Onvif protocol
- * Support WEB, CMS, VMS, MYEYE Platform
- * Mobile phone remote monitoring (iOS, Android)
- * Cloud services, P2P, alarm information push to phone
- * Support for more than twenty languages

Specifications

Product Name	WDM 32CH 4K-N 6 In 1 Hybrid 8HDD 2U CCTV Security Network Video Record DVR
Model No.	WDM-DVR6532K-GS

System

Processor	Hi3531D*2
-----------	-----------

Video

Video compression	H.265+/H.265/H.264
Encode	32*4M@8fps(6 in 1); 32*5M@6fps(6 in 1); 32*4K-N @7fps (6 in 1); 4M Default
Decode	16*4M@8fps(6 in 1); 8*5M@6fps(6 in 1); 8*4K-N @7fps (6 in 1); 4M Default
preview	32*4M@15fps(6 in 1); 32*5M@12fps(6 in 1); 32*4K-N @15fps (6 in 1); 4M Default
Multi-mode	Analog: 32*4M; 32*5M
	Digital Analog conversion: Support
	IP: 32*1080P/16*3M/8*5M
Playback	16/8CH

Audio

Audio compression	G.711A
-------------------	--------

Management

Record mode	Manual>Alarm>Motion detection>Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA

Interface

Video Input	32*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:4K)
VGA output	1*VGA (MAX:1080P)
Audio In/Out	16/1
Alarm In/Out	16/4
Ethernet	1*10/100Mbps Ethernet port, RJ45 port
PTZ Control	1*RS485, Support for multiple PTZ protocol
USB	2*USB2.0 ports
HDD	8*SATA interface (Up to 6TB)

General

Power supply	ATX Power Supply
Consumption	<10W (Without HDD)
Working temperature	0 °C - + 55 °C
Working humidity	10% -90% RH
Chassis	2U