

32chs 4K-N/5MP 4HDD Network P2P AHD CVI TVI CCTV DVR From ShenZhen Wardmay	
	
System	
Processor	Hi3531D*2
Model No.	WDM-DVR6532F-GS
Video compression	H.265+/H.265/H.264
Solution	32chs 4K-N/5.0 Megapixel(6fps)
Analog video input	32PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω
Audio compression	G.711A
Audio input	16CH IN/1 OUT
Alarm input	16CH IN/4 OUT
Video/Audio output	
Preview	32*4M@15fps(6 in 1)/32*5M@15fps(6 in 1)/ 32*4K-N@15fps(6 in 1), 4M default
Encoding resolution	32*4M@8fps(6 in 1)/32*5M@6fps(6 in 1)/ 32*4K-N@7fps(6 in 1), 4M default
Decoding resolution	16*4M@8fps(6 in 1)/8*5M@6fps(6 in 1)/ 8*4K-N@7fps(6 in 1), 4M default
Multimode input	Analog: 32*4M; 32*5M;
	Digital to analog conversion: support
	IP: 32*1080P/16*3M/8*5M
Simultaneous Playback	16/8CHS
HDMI/VGA output	800x600,1024x768,1280x1024,1440x900,720P,1080P
Frame rate	NTSC:1~30FPS/S;PAL:1~25FPS/S
Video bit rate	256kps/384Kbps/512Kbps/640kbps/768Kbps/1M/1.5M/2M/2.5M/3M/4M/5M/6M/8M
Video output	1CH video out
Dual-stream	YES
Stream type	combine streams/ video stream
Hard disk	4*SATA
Capacity	each port support max 8TB HDD
External interface	
Video mode	Manual recording > alarm recording > dynamic detection recording > timing recording
Video query	Time point retrieval, calendar retrieval, event retrieval, channel retrieval
Video Storage	Local hard disk storage, network storage
Backup	Network backup, USB backup, SATA burning
External interface	
Network interface	1PCS RJ45 10M / 100M/1000M adaptive Ethernet port
Serial interface	1PCS RS485/RS232
USB interface	2*USB2.0
Remote control	Yes
General	
Support	Support VGA,PTZ,HDMI
Remote control	Support mobile view (Android, iOS)
Browser access	Support IE, Chrome, Firefox, Safari
Language	Multiple language support
Power supply	DC12V6A
Working temperature	0℃--+55℃
Working humidity	10%--90%
Chassis	2U
Accessories	
Accessories	1pc power supply, remote controller, 1pc CD, 1pc user manual, 4pcs screws