



- * Support 4/8CHS 8.0MP/16CHS 5.0MP Encoding
- * Support Xvi, AHD, TVI, CVI, CVBS, IP video input
- * Support VGA maximum 1080P output, HDMI up to 4K output
- * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm
- * Support the Onvif protocol
- * Support WEB, CMS, VMS, MYEYE Platform
- * Mobile phone remote monitoring (iOS, Android)
- * Cloud services, P2P, alarm information push to phone
- * Support for more than twenty languages

Specifications

Product Name	High Quality Hybrid DVR 4/8CH 8MP 4K CCTV Security DVR From Wardmay Ltd	
Model No.	WDM-DVR6504T-GL	WDM-DVR6508T-GL
System		
Processor	Hi3521D	Hi3531D
Video		
Video compression	H.265+/H.265/H.264	
Encode	4*8M@8fps(6 in 1); 4*5M@14fps(6 in 1); 5MP default	8*8M@8fps(6 in 1); 8*5M@14fps(6 in 1); 5MP default
Decode	4*8M@8fps(6 in 1); 4*5M@14fps(6 in 1); 5MP default	4*8M@8fps(6 in 1); 8*5M@14fps(6 in 1); 5MP default
Multi-mode	Analog:4*8M; 4*5M	Analog:8*8M; 8*5M
	Hybird: 4*8M (analog) + 4*5M (network); 2*4K (analog) +2*4K (network)	Hybird: 8*5M (analog) +8*5M (network); 4*5M (analog) +4*5M (network)
	IP: 4*8M; 4*5M; 4*3M; 8*1080P+8*960P	IP: 8*3M ;4*5M
Playback	4/2CH	8/4CH
Audio		
Audio compression	G.711A	
Management		
Record mode	Manual>Alarm>Motion detection>Timing	
Inquire mode	Inquire by Time/Calendar/Event/Channel	
Storage mode	HDD Storage, Network Storage	
Backup	Network, USB, SATA	
Interface		
Video Input	4*BNC (Support Coaxitron)	8*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:4K)	
VGA output	1*VGA (MAX:1080P)	
Audio In/Out	4/1	
Alarm In/Out	0/0	
Ethernet	1*10/100Mbps Ethernet port, RJ45 port	
PTZ Control	1*RS485, Support for multiple PTZ protocol	
USB	2*USB2.0	
HDD	1*SATA interface (Up to 8TB)	
General		
Power supply	DC12V 2A	
Consumption	<10W(Without HDD)	
Working temperature	0°C--+55°C	
Working humidity	10%--90%	
Chassis	Mini 1 U	