

6” 18X Zoom 3.0MP Full Color Human Tracking Speed Dome PTZ IP Camera



Features

- * Support AI human tracking, simple operation, one touch trigger
- * 9pcs Warm light, Full Color Image for Day & Night, 18X optical Zoom
- * Full color night vision, high definition, High color reduction
- * Support AI human recognition algorithm, recognition speed is fast, high accuracy, and can be randomly selected warning area.Once someone breaks into the alert area, immediately trigger the sound and light alarm and linkage tracking
- * Support TSN private protocol, support standard ONVIF protocol
- * TF Card, Max 512G (Optional)
- * Support two-way audio, Voice alarm, alarm tone customization (Customers can record audio by themselves or use voice conversion tools to convert text into audio files in MP3 format, and upload
- * Support Mobile P2P Access of Android, IOS system
- * Support IP66 waterproof function, more applicable scenarios

Accessories

- Instruction book
- Warrant card
- Screw fittings

Product Name	H.265 18X Zoom 2.0MP Full Color Human Recognition and tracking Speed Dome IP Camera
Camera	
Model Number	WDM-IPL8817-18X
Main Solution	Hisilicom
Chip	Seetong Black Light Q30
Resolution	3.0MP
Warm Light	9pcs high performance warm light, ≥80m Night Vision
Electronic Shutter	Auto
DWDR	Support
Noise Reduction	2D, 3D
Lens	
Lens	Optical Zoom, f=4.7-84.6mm, D/N(ICR-Cut) , F1.6-F3.5
Viewing Angle	55.2°-3.2°(Wide Angle - far focus)
Leds	9pcs warmlight leds
Warmlight control	Auto/near light/far light/off
Video and Network	
Video Compression	H.265
Nework Protocols	Suppport HTTP, TCP/IP, IPv4, DHCP, NTP, RTSP, ONVIF, P2P, PPTP, GB/T28181, etc
Network interface	1ch 10/100BaseT Ethernet, RJ45, Lightning protection design
User management	Support multi-level user rights management
Mobile P2P	Support Android、IOS mobile access and “Seetong” PC management
Functions	
Rotation range	Horizontal: 0° ~ 360°; Vertical: -15° ~ 93°
Rotation speed	Keyborad control: Level: 45°/ s; Vertical: 30°/ s
Preset points	16
Audio	G.711 standard, Two Way Audio
Local Storage	Max 512G for optional
Human Tracking	Support, Automatic zoom to see face during tracking
Automatic Tracking Range	3M-80M
Regional Monitoring	Support
Custom Alarm Tone	Support
AB Two Point Scanning Bit	Arbitrary setting
Cruise	Support
Video Recording Color	Support, detect the key color mark of the human part video, and view it accurately
General	
Power	DC 12V3A(Contains infrared control circuit)
Consumption	≤25W
Work Environment	Temperature: -40°C~+60°C; Humidity: < 90%
IP Grade	IP66, 6000V lightning protection
Material	Cast aluminium
Bracket	Wall mounting