

4K 8MP HD Color Dome Camera Wired IP Camera for security



Features

- *Sony Blacklight Chips (IMX415)
- *Super clear day and night color image
- *Support ONVIF 2.4 protocol, H.265 profile
- *4mm Lens
- *Full color image for day and night
- *One way audio for optional

Dimension



Accessories

- User manual
- CD
- Screw

Specifications

Product Name	4K 8MP HD Color Dome Camera Wired IP Camera for security
Model No.	WDM-H265IP9800AL
Video	
System	Hisilicon high-performance DSP, HI351ARBCV300+Sony IMX415
Image Sensor	1/2.8" 4K 8.0M Pixel Sony IMX415 CMOS
Output resolution	3840(H)×2160(V)
Illumination	Color: 0.005Lux@F1.2(AGC ON), B/W: 0Lux(IR ON)
D/N mode	Auto IR-CUT switch, B/W, Color, Outer control
Signal Interface	2*PWM signal output, 1pc IR Cut port
Gain Control	Auto/ Manual
White Balance	Auto, Indoor, Outdoor, Sodium Lamp, Manual
DNR	Support 2DNR, 3DNR
Video Compression	H.265+/H.265/H.264
	AVI format, 2M~8Mbps adjustable;
Video Resolution	Main stream:3840×2160,2592×1944,2592×1520,2560×1440,2048×1520,2304×1296,1920×1080
	Sub stream: 800×448,720×480,640×480,640×360,480×360,352×288
Frame rate	8.0MP@20fps,support 7~20frame/seconds adjustable
Lens	
Lens	Standard 4mm lens(6mm lens optional)
View Angle	4mm lens(8MP F1.6 1/2.8" H 79.6°); 6mm lens(8MP F1.6 1/2.8" H 39.6°);
Leds	3pcs warmlight leds
Night Vision Distance	30m
Function	
Network interface	1pc RJ45 ethernet,10/100M;
ONVIF Protocol	Standard ONVIF Protocol
Network Protocols	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
Compatibility	Support HIKVISION, DAHUA, XM CMS, SEETONG UC2, Aebell NVR I8 ONVIF platform, NVR ONVIF protocol
OSD	Support Channel name, date on screen
Mobile P2P	Support Android, IOS visit
Normal	
Material	Metal Case, Black
Power	12V2A/POE(18W) optional
Working Temp	-20°C ~55°C
Working humidity	0%-90% RH(NO CONDENSING)