

1080P BlackLight Color Image Full Darkness IP Camera



Model	WDM-H265IP8200AL
	1080P BlackLight Color Image Full Darkness IP Camera
Image Sensor	1/2" 2.0M Pixel Sony IMX307 CMOS
Dynamic Range	100dB
SNR	≥50dB (AGC OFF)
Lens	4mm lens
Illumination	0.001Lux@F1.2 (Color Mode) ; 0.001 Lux@F1.2 (B&W mode) ; 0Lux (IR CUT ON)
D/N mode	Auto IR-CUT switch, B/W, Color, Outer control
Gain Control	Auto/ Manual
White Balance	Auto, Indoor, Outdoor, Sodium Lamp, Manual
DNR	Support 2DNR, 3DNR
Exposure Mode	Program mode (customizable shutter interval), shutter mode (1/5-1/20,000s), support slow shutter
Video Compression	H.265 Main Profile / H.264 High profile / M-JPEG
Max Resolution	1920x1080@25fps
Video Resolution	Main stream: 1920x1080、1280x960、1280x720、720x576、640x480
	Substream: 640x480、480x360、352x288、320x240、176x144、OFF
	MJPEG: 1280x720、OFF
Output code rate	CBR or VBR: 32K~10M
Leds	3pcs warm leds
Visit NO.	3 Users in Mainstream, 6 Users in Substream
Network Protocols	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
ONVIF Protocol	Standard ONVIF2.4
Compatibility	Support HIKVISION、DAHUA、XM CMS、SEETONG UC2、Aebell NVR I8 ONVIF platform、NVR ONVIF protocol
Mobile P2P	Support Android、IOS visit
Network interface	1ch 10/100BaseT Ethernet, RJ45
Power	12V2A/POE
Working Temp	-30°C ~60°C
Working humidity	0%-90% RH (NO CONDENSING)

Features

- *Super Chips (SONY 307)
- *Super clear day and night color image
- *Support ONVIF 2.4 protocol, H.265 profile
- *Color image for full night
- *One way audio for optional

Dimension

Accessories

- User manual
- CD
- Guarantee card
- Screw