

H.265 5.0MP Network Day and Night Color Security IP Camera



Features

- *Super SONY CMOS
- *Super clear day and night color image
- *Support ONVIF 2.4 protocol, H.265 profile
- *Full color image for day and night
- *4mm lens

Dimension



Accessories

- User manual
- CD
- Guarantee card
- Screw

Model	WDM-H265IP8500AL
	H.265 5.0MP Network Day and Night Color Security IP Camera
Dynamic Range	100dB
SNR	≥50dB (AGC OFF)
Lens	4mm lens
Illumination	0.001Lux@F1.2 (Color Mode) ; 0.001 Lux@F1.2 (B&W mode) ; 0Lux (IR CUT ON)
D/N mode	Auto IR-CUT switch, B/W, Color, Outer control
Gain Control	Auto/ Manual
White Balance	Auto, Indoor, Outdoor, Sodium Lamp, Manual
DNR	Support 2DNR, 3DNR
Exposure Mode	Program mode (customizable shutter interval), shutter mode (1/5-1/20,000s), support slow shutter
Video Compression	H.265 Main Profile / H.264 High profile / M-JPEG
Max Resolution	2592*1944@15fps
Video Resolution	Main stream: 2599x1944 、 1920x1080、 1280x960、 1280x720、 720x576、 640x480
	Substream: 2599x1944 、 640x480、 480x360、 352x288、 320x240、 176x144、 OFF
	MJPEG: 1280x720、 OFF
Output code rate	CBR or VBR: 32K~10M
Leds	3pcs warm leds
Visit NO.	3 Users in Mainstream, 6 Users in Substream
Network Protocols	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
ONVIF Protocol	Standard ONVIF2.4
Compatibility	Support HIKVISION、 DAHUA、 XM CMS、 SEETONG UC2、 Aebell NVR I8 ONVIF platform、 NVR ONVIF protocol
Mobile P2P	Support Android、 IOS visit
Network interface	1ch 10/100BaseT Ethernet, RJ45
Power	12V2A/POE
Working Temp	-30°C ~60°C
Working humidity	0%-90% RH (NO CONDENSING)