

**H.265 4K 8.0MP Blacklight Full Color Day & Night Outdoor Bullet IP Camera**



**Features**

- \*Sony Chips (IMX415)
- \*Super clear day and night color image
- \*Support ONVIF 2.4 protocol, H.265 profile
- \*4mm Lens
- \*Full color image for day and night

**Dimension**



**Accessories**

- User manual
- CD
- Screw

**Specifications**

|                       |  |
|-----------------------|--|
| Product Name          | <b>H.265 4K 8.0MP Blacklight Full Color Day &amp; Night Outdoor Bullet IP Camera</b>   |
| Model No.             | WDM-H265IP8800AL   |
| <b>Video</b>          |  |
| Image Sensor          | 1/2.8" 4K 8.0M Pixel Sony IMX415 CMOS  |
| Output resolution     | 3840(H)×2160(V)  |
| Illumination          | Color: 0.005Lux@F1.2(AGC ON), B/W: 0Lux(IR ON)   |
| D/N mode              | Auto IR-CUT switch, B/W, Color, Outer control  |
| Signal Interface      | 2*PWM signal output, 1pc IR Cut port   |
| Gain Control          | Auto/ Manual   |
| White Balance         | Auto, Indoor, Outdoor, Sodium Lamp, Manual   |
| DNR                   | Support 2DNR, 3DNR   |
| Video Compression     | H.265+/H.265/H.264<br>AVI format, 2M~8Mbps adjustable;   |
| Video Resolution      | Main stream:3840×2160,2592×1944,2592×1520,2560×1440,2048×1520,2304×1296,1920×1080<br>Sub stream: 800×448,720×480,640×480,640×360,480×360,352×288 |
| Frame rate            | 8.0MP@20fps,support 7~20frame/seconds adjustable   |
| <b>Lens</b>           |  |
| Lens                  | Standard 4mm lens(6mm lens optional)   |
| View Angle            | 4mm lens(8MP F1.6 1/2.8" H 79.6°); 6mm lens(8MP F1.6 1/2.8" H 39.6°);  |
| Leds                  | 3pcs warmlight leds  |
| Night Vision Distance | 30m  |
| <b>Function</b>       |  |
| Network interface     | 1pc RJ45 ethernet,10/100M;   |
| ONVIF Protocol        | Standard ONVIF Protocol  |
| Network Protocols     | TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P  |
| Compatibility         | Support HIKVISION, DAHUA, XM CMS, SEETONG UC2, Aebell NVR I8 ONVIF platform, NVR ONVIF protocol  |
| OSD                   | Support Channel name, date on screen   |
| Mobile P2P            | Support Android, IOS visit   |
| <b>Normal</b>         |  |
| Material              | Metal Case, Black  |
| Power                 | 12V2A/POE(18W) optional  |
| Working Temp          | -20°C ~55°C  |
| Working humidity      | 0%-90% RH(NO CONDENSING)   |