

3MP HD DUAL LIGHT WIFI/POE CAMERA

Model: WDM-HD65F-WF-ST



Features:

- AI human tracking, easy to operate
- Dual Light. Turn on white light when people are detected at night
- 6KV lightning strike protection
- IP66 Rating
- Wired network port output; Connect to "Seetong" NVR easily
- TF Card up to 512G
- Two way audio
- Support POE
- Easy WIFI connection
- Intelligent voice prompts

Technical Specifications

Model NO.	WDM-HD65F-WF-ST
Camera	
Image Sensor	1/2.7" CMOS
Solution	SSC335 + SC3335
Digital Noise Reduction	2D and 3D DNR
General Function	Horizontal flip and vertical flip
Lightning Protection	Lightning Protection 6000V, Comprehensive lightning protection of power supply and network, passed ITU-T K.21-2008, IEC61000-42/IEC61000-4-5 and other lightning protection standards
Business Function	Support: OSD, real-time video transmission, intelligent detection and alarm linkage, and "Seetong" cloud service
Lens	
Lens Focal Length	F2.0, 4mm fixed lens
Field of View	Diagonal: 107°, Horizontal Field: 89°, Vertical Field: 48°
PTZ Control	
Control Angle	Pan: 0- 340° Tilt: 0-105 °
Control Speed	Pan: 25°/s Tilt: 20°/s
Video	
Video Compression	Supports:H.265+/H.265/H.264; Support dual stream and the stream 500~8000kbps adjustable; Support PAL and NTSC System
Frame Rate	3 MP: 20fps, 7~20 fps adjustable

Image Output	Main Stream: 2304*1296, 1920*1080, 1280*720
	Sub-Stream: 800*448, 640*480, 640*360, 352*288
Audio	
Audio Compression	G.711, support two way audio
Sampling Frequency	8KHz
Code Ratio	64KHz
Intelligent	
General	Human detection and human tracking
Alarm	SD card recording, APP alarm, Sound and Light Alarm
Network	
Protocols	TPS,TCP/IP, IPv4, DHCP, RTSP, P2P
APP	
Mobile View	Android, IOS (APP: Seetong)
Interface	
Communication Interface	1 RJ45 10 M / 100 M Ethernet interface
TF Card Slot	Supports (Max 512G)
Microphone	Built in
Speaker	Built in
WiFi Module	DC3.3V WiFi Module; Support 2.4G frequency
Light	
White Light Distance	Up to 15m
IR Distance	Up to 15m
LEDS	4 IR LEDS+ 4 Warm Light LEDS
PTZ Function	
Preset	16 pcs
AB Scan/Tour	Not supported
Auto Tracking Distance	3M-30M
General	
Power Supply	DC: 12V±25%
Power Connector	Φ5.5mm circular interface
Operating Conditions	(-20°C ~ 50°C) humidity 95% or less (non-condensing)
Power consumption	Max. 9.72W
Factory Reset	Support
Material	Half Metal Housing
Dimension	98*165.5*146mm
Weight	NW: 450g
Weather Proof Rating	IP66
Dimension	

