



Specification

Product Name	2.0/5.0MP USB2.0/Type-C Mini Camera	
Model No.	WDM-V6008E	WDM-V6008H
Pixel Size	2.8μm x 2.8μm Square Pixel	1.4μm x 1.4μm Square Pixel
Lens Size	1/2.9-inch COMS SC2053	1/4-inch COMS OV5693
Lens	3.6mm Lens(Standard), Wide View / Fisheye Lens available for customization	
Active Pixel Array	2.0MP(1920H*1080V)	5.0MP(2592H*1944V)
Frame rate	Full @ 30 FPS	
Output image format	MJPEG/YUV2	
Resolution and frame rate	320x240MJPG@30fps / 640x360 MJPG@30fps / 1028x720 MJPG@30fps / 960x540P MJPG@30fps / 640X480 MJPG@30fps / 1920*1080 MJPG@30fps / 2592*1944 MJPG@30fps.	
Interface type	USB2.0 Cable Or Type-C Output	
No-drive protocol	USB Video Class(UVC)	
Adjustable parameter	Brightness, contrast, color saturation, clarity , sharpness, gamma, white balance, inverse contrast, exposure	
Night Vision	No (standard), support 850 or 940nm led board for customization	
Power Supply	DC 5V	
Power Consumption	<150mW	
Stable Temperature	0~60°	
Size	34*34、42*42、40*45 (mm)	
Features	support RTMP Push streaming, to achieve remote synchronous viewing	
Supported system	WinXp/Visata/Win7/Win8/Win8....., Linux With UVC (above linux-4.0), MAC-OS X 10.4.8 or later	