Wardmay[®] HD CCTFV Total Solution www.wardmay.com

316L Stainless Steel Explosion-Proof CCTV Mini Camera For Marine, Gas Station



Features

700TVL/1080P High Resolution

* 4/6mm lens for optional

* Explosion-proof housing

⁴ 316L stainless steel surface treated with fluorinecarbon spray. elegant structure. explosion proof,

dust proof, water proof, rust-proof...

 * Optional temperature controlled SCR semiconductor module to realize automatic heating and cooling functions..heater turned on when temperature lower than -10 degree +-5 degree
* Can be installed on the market 80% camera

* We can customize right camera size according to

your requirement

Camera		
Model	WDM-EX700WB/316L	WDM-EX200HB/316L
Sensor	Color 1/3" CCD	1/2.8" CMOS
System	PAL/NTSC	
Resolution	700TVL	1080P
Effective pixels	PAL: 795(H)×596(V) / NTSC: 811(H) * 508(V)	1920(H)x1080(V)
S/N Ratio	52dB(Min)/60dB(Max)(AGC ON/OFF)	52dB(Min)/60dB(Max)(AGC ON/OFF)
Lens	4/6mm lens for optional	
IR Distance	30-60M IR Range	
Signal-to-Noise Ratio	>50db	
Electrical Connectivity	Composite cable	
Rated Temperature	-30 degree ~ +70 degree	
Atmospheric Pressure	86~106kpa	
Relative Humidity	<=95%RH(+-25 degree)	
Material	316L Stainless steel	
Ingress Protection	IP68	
Interface spec	G-1/2"	
Method of installation	bracket mount	
Atex Mark	II 2G Ex db IIC T6 Gb, II 2D Ex tb IIIC(85 degree) Db	
IEC Mark	Ex dIIC T6 Gb/DIP A20 TA, T6	
Input Voltage	DC12V	
Working Current	<=1A	