

### 1080P BlackLight Color Image Full Darkness IP Camera



#### Features

- \*Super Chips (SONY 307)
- \*Super clear day and night color image
- \*Support ONVIF 2.4 protocol, H.265 profile
- \*Standard one way audio
- \*Color image for full night

#### Dimension



#### Accessories

- User manual
- CD
- Guarantee card
- Screw

<b>Model</b>	WDM-H265IP8200BL
	1080P BlackLight Color Image Full Darkness IP Camera
<b>Image Sensor</b>	1/2" 2.0M Pixel Sony IMX307 CMOS
<b>Dynamic Range</b>	100dB
<b>SNR</b>	≥50dB (AGC OFF)
<b>Lens</b>	4mm lens
<b>Illumination</b>	0.001Lux@F1.2 (Color Mode) ; 0.001 Lux@F1.2 (B&W mode) ; 0Lux (IR CUT ON)
<b>D/N mode</b>	Auto IR-CUT switch, B/W, Color, Outer control
<b>Gain Control</b>	Auto/ Manual
<b>White Balance</b>	Auto, Indoor, Outdoor, Sodium Lamp, Manual
<b>DNR</b>	Support 2DNR, 3DNR
<b>Exposure Mode</b>	Program mode (customizable shutter interval ), shutter mode (1/5-1/20,000s), support slow shutter
<b>Video Compression</b>	H.265 Main Profile / H.264 High profile / M-JPEG
<b>Max Resolution</b>	1920x1080@25fps
<b>Video Resolution</b>	Main stream: 1920x1080、1280x960、1280x720、720x576、640x480
	Substream: 640x480、480x360、352x288、320x240、176x144、OFF
	MJPEG: 1280x720、OFF
<b>Output code rate</b>	CBR or VBR: 32K~10M
<b>Leds</b>	5pcs warm leds
<b>Visit NO.</b>	3 Users in Mainstream, 6 Users in Substream
<b>Network Protocols</b>	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
<b>ONVIF Protocol</b>	Standard ONVIF2.4
<b>Compatibility</b>	Support HIKVISION、DAHUA、XM CMS、SEETONG UC2、Aebell NVR I8 ONVIF platform、NVR ONVIF protocol
<b>Mobile P2P</b>	Support Android、IOS visit
<b>Network interface</b>	1ch 10/100BaseT Ethernet, RJ45
<b>Power</b>	12V2A/POE
<b>Working Temp</b>	-30°C ~60°C
<b>Working humidity</b>	0%-90% RH (NO CONDENSING)