

## 3MP Wireless PTZ CCTV Camera System with Alarm Lamp



### Features

- \*WiFi connection, plug and play
- \*Camera comes with alarm lamp, red and blue lights flash
- \*Standard ONVIF Protocol, RJ45 for standard
- \*Support 3D Human Auto Tracking
- \*Support double light function, detect human and turn on warm light;
- \*IP66 waterproof level, available to use in serious environment and special scene
- \*Support two way audio
- \*Application: warehouse, office, shop, supermarket, villa, Park, etc
- \* App: **Camhi Pro: P6SLite**

### Dimension



### Accessories

- User Manual
- CD
- Screw fittings

#### Specification

Product Name	<b>2MP Wireless PTZ CCTV Camera System with Alarm Lamp</b>
Model No.	WDM-IP3018W-WF/P
<b>Camera</b>	
System	Hisilicon high-performance DSP, Hi3516E+F37H
Sensor	1/2.9" 2.0MP Progressive CMOS Image Sensor
Output resolution	1920(H)×1080(V)
Rotate	Pan: 0-360 degree; Tilt: 0-93 degree;
Rotating speed	0-80°/s for Pan; 0-45°/s for Tilt;
Presets	256PCS
<b>Lens</b>	
Lens	18X Zoom Lens (6mm-108mm lens)
IR distance	4pcs warm leds +8pcs ir leds
<b>Video &amp; Audio</b>	
Video processing	H.264/H.265M-JPEG, dual streaming, three streaming
Human Auto Tracking	Support
Two way audio	support, built-in for standard
Audio Compression	G711, PCM
<b>WiFi and Network</b>	
WiFi Protocol	IEEE 802.11b/g
WiFi Distance	Open Space ≥120M
WiFi antenna	Enhanced 3db antenna
TF card storage	Supports 128GB
Network interface	RJ45 ethernet,10/100M;
Network Protocol	Onvif; P6S; MouKang
Network Safe	HTTPS, 802.1X、 IP ADDRESS FILTERING
Network interface	Support Android\iPhone
App	<b>P6SLite</b>
<b>Function</b>	
Function	Lightning protection, 3000V instant
	Support Mechanical zero calibration
<b>Normal</b>	
Power supply	DC12V2A/POE(optional), ≤10W power consumption
Operation temperature	-30°C~+60°C