

**China IP Camera Wireless 2/5MP Vandalproof Dome Indoor Surveillance**



**Features**

- \*Hisilicon high-performance DSP
- \*H.265/H.264 High profile
- \*Support dual stream, support mobile phone
- \*Support power supply DC12V/POE
- \*Standard ONVIF Protocol
- \*Complete SDK for second development.
- Support multi network protocols
- \*Provide a unified free client to achieve video recording/playback/preview
- \*Support ICR filter switching function, day and night surveillance
- \* **App: Camhi Pro**

**Dimension**



**Accessories**

- User Manual
- CD
- Screw fittings

**Specification**

Product Name	<b>China IP Camera Wireless 2/5MP Vandalproof Dome Indoor Surveillance</b>	
Model No.	WDM-IP7764Q-W	WDM-IP7764H-W
<b>Camera</b>		
System	Hisilicon high-performance DSP, Hi3516EV300+SONY 335 (128G)	Hisilicon high-performance DSP, Hi3516EV200+SONY307 (64G)
Sensor	1/2.7" 5.0MP Progressive CMOS Image Sensor	1/3" 2.0MP Progressive CMOS Image Sensor
Output resolution	2592(H)×1944(V)	1920(H)×1080(V)
D/N Mode	Auto switching,black and white vide and IR cut action linkage	
Illumination	Color: 0.01lux@F1.2; B/W: 0lux(IR ON)	
<b>Lens</b>		
Lens	3.6/4/6mm fixed lens	
IR distance	20m(2pcs IR Array leds)	
<b>Video &amp; Audio</b>		
Video processing	H.265/H.264 video compression, dual streaming	
Video Output	Mainstreaming: 2592*1520,2018*1536, 1920x1080,1280x960,1280x720, 1024x768,1280x720; Sub streaming: 960*540,640*360, 480x270,352x288,320x240,352x192,	Mainstreaming: 1920x1080,1280x960,1280x720, 1024x768,1280x720; Sub streaming: 960*540,640*360, 480x270,352x288,320x240,352x192, 320x192,288x192,256x192
Frame rate	5.0MP 25/30 frame(full real time), support 1~30frame/seconds adjustable	2.0MP 25/30 frame(full real time), support 1~30frame/seconds adjustable
Audio Compression	AAC	
<b>WiFi and Network</b>		
WiFi Protocol	IEEE 802.11b/g	
WiFi Safe mode	WEP/WPA/WPA2	
WiFi antenna	Enhanced 5db antenna	
TF card storage	Supports 128GB	Supports 64GB
Network interface	RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol	
Access Protocol	Standard ONVIF Protocol, Support third party access; PC;	
	Support IE6.0 and above Smartphone	
	Support Android\iPhone	
App	Camhi Pro	
<b>Function</b>		
Function	Support WEB configuration, OSD,real-time video transmission	
	Support motion detection	
	Support front end storage, playback and download	
	Support uniform client and platform system application	
	Support complete SDK for second development.	
<b>Normal</b>		
Power supply	DC12V/POE(optional)	
Operation temperature	-10°C~+60°C,10%~90%RH	