

H.265 2.0/5.0MP IR Dome IP Security Surveillance HD Wifi Camera



Features

- *Hisilicon high-performance DSP
- *High quality progressive scanning CMOS
- *H.265/H.264 High profile
- *Support dual stream, support mobile phone
- *Support power supply DC12V/POE
- *Standard ONVIF Protocol
- *Complete SDK for second development. Support multi network protocols
- *Provide a unified free client to achieve video recording/playback/preview
- *Support ICR filter switching function, day and night surveillance
- * Built-in microphone and speaker, support two-way audio**
- * App: Camhi Pro**

Dimension



Accessories

- User Manual
- CD
- Screw fittings

Specification

Product Name	H.265 2.0/5.0MP IR Dome IP Security Surveillance HD Wifi Camera	
Model No.	WDM-IP8601H-W	WDM-IP8601Q-W
Camera		
System	Hisilicon high-performance DSP, Hi3516EV100+Sony307	Hisilicon high-performance DSP, Hi3516EV300+Sony335
Sensor	1/2.8" 2.0MP Progressive CMOS Image Sensor	1/2.7" 5.0MP Progressive CMOS Image Sensor
Output resolution	1920(H)×1080(V)	2592(H)×1944(V)
D/N Mode	Auto switching,black and white vide and IR cut action linkage	
Illumination	Color: 0.01lux@F1.2; B/W: 0lux(IR ON)	
Lens		
Lens	Wide-Angle Lens	
IR distance	20m(2pcs IR Array leds)	
Video & Audio		
Video processing	H.265/H.264 video compression, dual streaming	
Video Output	Main streaming: 1920*1080,1280*960, 1280*720,1024*768,1280*720; Sub streaming: 960*540,640*360, 480*270,352*288,320*240,352*192, 320*192,288*192,256*192	Mainstreaming:2592*1520,2018*1536, 1920x1080,1280x960,1280*720, 1024*768,1280*720; Sub streaming: 960*540,640*360, 480*270,352*288,320*240,352*192, 320*192,288*192,256*192
Frame rate	2.0MP 25/30 frame(full real time), support 1~30frame/seconds adjustable	4.0MP 25/30 frame(full real time), support 1~30frame/seconds adjustable
Voice intercom	Built-in microphone and speaker	
Audio Compression	AAC	
WiFi and Network		
WiFi Protocol	IEEE 802.11b/g	
WiFi Safe mode	WEP\WPA\WPA2	
WiFi antenna	Built-in antenna	
TF card storage	Supports 64GB	Supports 128GB
Network interface	RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol	
Access Protocol	Standard ONVIF Protocol, Support third party access; PC;	
	Support IE6.0 and above Smartphone	
	Support Android\iPhone	
App	Camhi Pro	
Function		
Function	Support WEB configuration, OSD,real-time video transmission	
	Support motion detection	
	Support front end storage ,playback and download	
	Support uniform client and platform system application	
	Support complete SDK for second development.	
Normal		
Power supply	DC12V/POE(optional)	
Operation temperature	-10°C~+60°C,10%~90%RH	