

## 4CH WiFi Home Security Camera Wireless (Model: WDM-NKITR04BWL-10)



- \* 4CH 3MP WiFi NVR With 10" LCD Screen
- \* 2 indoor camera, 2 outdoor camera with adaptor, bracket.
- \* Plug and Play, no need network paring
- \* Strong ability of signal transmit up to crossing 1 to 4 walls, wifi distance:80-300 meters in open space
- \* APP: Esee Cloud

### IP Cameras specifications

Operating System	Embedded linux
Image Sensor	1/2.8" Progressive Scan Sensor
Resolution	3MP
Frame Specification	H.265 3MP@18fps
S/N Ratio	>39.1dB
Minimum Illumination	Color:0.1 Lux; B/W:0.01 Lux
Lens	110 wide angle lens for dome camera, 4mm for bullet
Infrared distance	20-30m
Waterproof	IP66
White Balance	Auto
Day&Night	IR cut filter with auto switch
3D-DNR	Auto
Privacy Masking	4 Zone Selectable
Infrared lamp	2pcs leds for dome; 3pcs leds for bullet
Power Input	DC12V1A (4pcs)
Consumption	max 6W
Interface	RJ45/WIFI 802.11b/g/n
Operation temperature	-10°C to +50°C /30% to 80% RH

### WIFI NVR Specifications

#### System

Display	10" LCD Screen
Operating System	Embedded linux OS
Main processor	Hi 3536D
System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup

#### Interface

Operator interface	16-bit true color graphic menu operation interface, support mouse operation
Preview	1/4
Video input (IP)	4*3MP
Access bandwidth	24Mbps
Forwarding bandwidth	25Mbps
Video compression	H.265+
Display quality	Max 3MP
Playback quality	2/3MP
Decode	4*3MP
VR	Unsupport
Motion detection	Support(depend on camera)

#### Audio

Audio compression	G.711A
Intercom	Unsupport

#### Record & playback

Recording mode	Manual>Alarm>Dynamic Detection>Timing
Local payback	4*3MP
Search mode	Search by Time/Calendar/Event/Channel
Record storage	HDD、 Network
Backup mode	Network backup, USB hard disk, USB burner, SATA burner

#### External Interface

Video output	1ch VGA, 1ch HDMI HD output
Audio I/O	0/0
Alarm I/O	0/0
Network interface	1*RJ45 10M/100M Adaptive Ethernet port+4ch WIFI
USB interface	2*USB2.0 ports
HDD	1* SATA(Up to 6TB for each disk)
ESATA	No
Serial interface	No

#### Other

ONVIF	No
Power supply	12V/2A
Power Consumption	<10W(Without HDD)
Work environment	Temperature:0°C- + 55°C , Humidity:10%- 90%RH , Atm:86kpa- 106kp

### Package Informations

Wifi NVR	1 set
Camera	4 pieces
Network line	1m*1
Power adapter	DC12V2A(1 pcs); DC12V1A(4 pcs)
USB Mouse	1 piece
User Manual	1 piece
Screw bag	4 pieces